



US006957631B2

(12) **United States Patent**
Jacobsen et al.

(10) **Patent No.:** **US 6,957,631 B2**
(45) **Date of Patent:** **Oct. 25, 2005**

(54) **RAPID RESPONSE POWER CONVERSION DEVICE**

(75) Inventors: **Stephen C. Jacobsen**, Salt Lake City, UT (US); **Marc Olivier**, Sandy, UT (US)

(73) Assignee: **Sarcos Investments LC**, Salt Lake City, UT (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 176 days.

(21) Appl. No.: **10/190,336**

(22) Filed: **Jul. 5, 2002**

(65) **Prior Publication Data**

US 2003/0005896 A1 Jan. 9, 2003

Related U.S. Application Data

(60) Provisional application No. 60/303,053, filed on Jul. 5, 2001.

(51) **Int. Cl.⁷** **F02M 23/00**

(52) **U.S. Cl.** **123/46 R**

(58) **Field of Search** 123/78 A, 48 A, 123/531, 46 R, 46 E, 78 AA; 417/380, 379, 381, 390

(56) **References Cited**

U.S. PATENT DOCUMENTS

179,782 A * 7/1876 Gilles 123/46 R
3,170,406 A 2/1965 Robertson
3,234,395 A 2/1966 Colgate

3,868,931 A 3/1975 Dutry et al.
4,167,922 A 9/1979 Doundoulakis
5,109,810 A 5/1992 Christenson
5,685,215 A 11/1997 Jepsen et al.
5,894,730 A 4/1999 Mitchell
6,241,488 B1 6/2001 Luoto
6,244,226 B1 6/2001 Berlinger et al.
6,626,650 B1 * 9/2003 Kenchington et al. 417/416


* cited by examiner

Primary Examiner—Tony M. Argenbright
Assistant Examiner—Hyder Ali
(74) *Attorney, Agent, or Firm*—Thorpe North & Western, LLP

(57) **ABSTRACT**

An apparatus and method for extracting energy from an internal combustion engine includes a chamber having a primary piston and a secondary piston with a combustion portion of the chamber situated adjacently between the primary piston and secondary piston. The secondary piston includes a substantially lesser mass than that of the primary piston. The chamber includes at least one fluid port for supplying fuel to the combustion portion and an out-take port for releasing combusive exhaust. The chamber includes a controller for controlling the combustion therein at selected cycles of the primary piston. The secondary piston is configured to draw a portion of energy from combustion controlled by the controller in the chamber. Such portion of energy is provided with a rapid response to an energy transferring portion interconnected to the secondary piston, which in turn, transfers and/or converts the energy for acting on a load or external application.

40 Claims, 8 Drawing Sheets






Fig.1




Fig. 2




Fig. 3




Fig. 4




Fig. 5




Fig. 6




Fig. 7




Fig. 7A




Fig. 8




Fig. 9

RAPID RESPONSE POWER CONVERSION DEVICE

Priority of application No. 60/303,053 filed Jul. 5, 2001
in the US Patent Office is hereby claimed.

BACKGROUND OF THE INVENTION

1. Field of the Invention

The present invention relates generally to internal combustion engines. More specifically, the present invention relates to an apparatus and method of extracting energy from combustion in an internal combustion engine.

2. Related Art

Primary power sources that directly convert fuel into usable energy have been used for many years in a variety of applications including motor vehicles, electric generators, hydraulic pumps, etc. Perhaps the best known example of a primary power source is the internal combustion engine, which converts fossil fuel into rotational power. Internal combustion engines are used by almost all motorized vehicles and many other energetically autonomous devices such as lawn mowers, chain saws, and emergency electric generators. Converting fossil fuels into usable energy is also accomplished in large electricity plants, which supply electric power to power grids accessed by thousands of individual users. While primary power sources have been successfully used to perform these functions, they have not been successfully used independently in many applications because of their relatively slow response characteristics. This limitation is particularly problematic in powering robotic devices and similar systems which utilize a feedback loop which makes real time adjustments in movements of the mechanical structure. Typically, the power source in such a system must be able to generate power output which quickly applies corrective signals to power output as necessary to maintain proper operation of the mechanical device.

The response speed of a power source within a mechanical system, sometimes referred to as bandwidth, is an indication of how quickly the energy produced by the source can be accessed by an application. An example of a rapid response power system is a hydraulic power system. In a hydraulic system, energy from any number of sources can be used to pressurize hydraulic fluid and store the pressurized fluid in an accumulator. The energy contained in the pressurized fluid can be accessed almost instantaneously by opening a valve in the system and releasing the fluid to perform some kind of work, such as extending or retracting a hydraulic actuator. The response time of this type of hydraulic system is very rapid, on the order of a few milliseconds or less.

An example of a relatively slow response power supply system is an internal combustion engine. The accelerator on a vehicle equipped with an internal combustion engine controls the rotational speed of the engine, measured in rotations per minute ("rpms"). When power is desired the accelerator is activated and the engine increases its rotational speed accordingly. But the engine cannot reach the desired change in a very rapid fashion due to inertial forces internal to the engine and the nature of the combustion process. If the maximum rotational output of an engine is 7000 rpms, then the time it takes for the engine to go from 0 to 7000 rpms is a measure of the response time of the engine, which can be a few seconds or more. Moreover, if it is attempted to operate the engine repeatedly in a rapid cycle from 0 to 7000 rpms and back to 0 rpms, the response

time of the engine slows even further as the engine attempts to respond to the cyclic signal. In contrast, a hydraulic cylinder can be actuated in a matter of milliseconds or less, and can be operated in a rapid cycle without compromising its fast response time.

For this reason, many applications utilizing slow response mechanisms require the energy produced by a primary power source be stored in another, more rapid response energy system which holds energy in reserve so that the energy can be accessed instantaneously. One example of such an application is heavy earth moving equipment, such as backhoes and front end loaders, which utilize the hydraulic pressure system discussed above. Heavy equipment is generally powered by an internal combustion engine, usually a diesel engine, which supplies ample power for the operation of the equipment, but is incapable of meeting the energy response requirements of the various components. By storing and amplifying the power from the internal combustion engine in the hydraulic system, the heavy equipment is capable of producing great force with very accurate control. However, this versatility comes at a cost. In order for a system to be energetically autonomous and be capable of precise control, more components must be added to the system, increasing weight and cost of operation of the system.

Another example of a rapid response power supply is an electrical supply grid or electric storage device such as a battery. The power available in the power supply grid or battery can be accessed as quickly as a switch can be opened or closed. A myriad of motors and other applications have been developed to utilize such electric power sources. Stationary applications that can be connected to the power grid can utilize direct electrical input from the generating source. However, in order to use electric power in a system without tethering the system to the power grid, the system must be configured to use energy storage devices such as batteries, which can be very large and heavy. As modern technology moves into miniaturization of devices, the extra weight and volume of the power source and its attendant conversion hardware are becoming major hurdles against meaningful progress.

The complications inherent in using a primary power source to power a rapid response source become increasingly problematic in applications such as robotics. In order for a robot to accurately mimic human movements, the robot must be capable of making precise, controlled, and timely movements. This level of control requires a rapid response system such as the hydraulic or electric systems discussed above. Because these rapid response systems require power from some primary power source, the robot must either be part of a larger system that supplies power to the rapid response system or the robot must be directly fitted with heavy primary power sources or electric storage devices. Ideally, however, robots and other applications should have minimal weight, and should be energetically autonomous, not tethered to a power source with hydraulic or electric supply lines. To date, however, technology has struggled to realize this combination of rapid response, minimal weight, effective control, and autonomy of operation.

SUMMARY OF THE INVENTION

The present invention relates to an apparatus and method for extracting a portion of energy from the energy created during combustion in an internal combustion engine. The present invention is directed to extracting a portion of energy during an optimal time period of combustion and providing superior bandwidth characteristics to the engine.

The present invention includes a chamber having a primary piston, a rapid response component and a controller operably interconnected to the chamber. The chamber also includes at least one fluid port for supplying fluid thereto and an out-take port. The primary piston in combination with the fluid port is configured to provide a variable pressure to the chamber and at least partially facilitate combustion to create energy in a combustion portion of the chamber. The primary piston is configured to reciprocate in the chamber. The controller is configured to control the combustion in the chamber. The rapid response component is in fluid communication with the chamber so that the rapid response component is situated adjacent the combustion portion of the chamber. According to the present invention, the rapid response component is configured to draw a portion of the energy from the combustion in the chamber.

One aspect of the present invention provides that the portion of energy drawn from the combustion by the rapid response component is drawn from a proximate instant of the combustion and prior to the primary piston being positioned at a median between a top dead center position and a bottom dead center position in the chamber. Furthermore, the rapid response component draws at least 90% of the portion of the energy from the chamber within 45 degrees of the primary piston descending from the top dead center position. As such, a majority of the portion of energy extracted by the rapid response component is completed relatively long before the primary piston completes a reciprocation cycle.

The rapid response component includes a secondary piston having an energy receiving portion. The secondary piston is interconnected to an energy transferring portion, wherein the energy receiving portion of the secondary piston is configured to draw the portion of the energy from the combustion and transfer such energy to the energy transferring portion of the rapid response component. At the energy transferring portion, the portion of energy extracted from the combustion is converted to any one of hydraulic energy, pneumatic energy, electric energy and mechanical energy.

Another aspect of the present invention provides that as the linear movement of the primary piston between the top and dead center positions is always substantially constant, the linear movement of the secondary piston is variable in length. Such variable length is determined by at least a load to which the portion of the energy is acting upon. Furthermore, the effective inertia of the primary piston is greater than the effective inertia of the secondary piston by a ratio of at least 5:1. Such ratio is the case at least during the time in which the portion of energy is being extracted to the secondary piston.

The controller is configured to control combustion in the chamber. In particular, depending on the load and/or requirements of the internal combustion engine, the controller is configured to control and select particular cycles for initiating combustion out of the substantially continuously repeating cycles of the primary piston reciprocating in the chamber. As such, the controller is configured to control the energy extracted by the secondary piston to provide an impulse modulation and/or amplitude modulation of energy. As such, the ability to select particular cycles and, thus, the ability to rapidly provide energy and terminate the energy from cycle to cycle provides superior bandwidth than the bandwidth provided from the primary piston.

In one embodiment, the chamber primarily includes a single compartment housing both the primary piston and the rapid response component. The rapid response component

includes a secondary piston, wherein the secondary piston and primary piston face each other with the combustion portion in the chamber therebetween.

In a second embodiment, the chamber includes a first compartment and a second compartment with a divider portion dividing the compartments and an aperture defined in the divider portion and extending between the first and second compartments. With this arrangement, the fluid is compressed by the primary piston from the first compartment to the second compartment through the aperture, wherein the controller ignites the compressed fluid in the second compartment. In the second embodiment, the combustion is at least partially isolated from the primary piston.

In a third embodiment, the present invention is directed to a rapid response component associated with a non-combustion system. In this system, a reactive member, such as a catalyst, is positioned in the chamber. The reactive member is positioned in the chamber and configured to receive a fluid, such as a monopropellant or hydrogen peroxide, to produce a non-combustive reaction which provides energy and a variable pressure to the chamber for reciprocating the primary piston. The controller is configured to control the non-combustive reaction by controlling the fluid entering the chamber. The rapid response component is situated adjacent a portion of the chamber having the non-combustive reaction so that the rapid response component is configured to draw and extract a portion of the energy for the non-combustive reaction.

Other features and advantages of the present invention will become apparent to those of ordinary skill in the art through consideration of the ensuing description, the accompanying drawings, and the appended claims.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 illustrates a schematic side view of a rapid response energy extracting system, depicting a chamber having a primary piston and a secondary piston, according to a first embodiment of the present invention;

FIG. 2 illustrates a block diagram associated with various partial schematic side views, depicting various forms of energy transfer through an energy transfer portion of the rapid response energy extracting system, according to the first embodiment of the present invention;

FIG. 3 illustrates a partial schematic side view of the rapid response energy extracting system, depicting a chamber having multiple compartments, according to a second embodiment of the present invention;

FIG. 4 illustrates a graphical representation of physical response characteristics of the primary piston with respect to the secondary piston in terms of time, temperature and displacement of the primary and secondary pistons, according to the present invention;

FIG. 5 illustrates a graphical representation of the physical response characteristics of the primary piston with respect to the secondary piston, depicting impulse modulation of the secondary piston, according to the present invention;

FIG. 6 illustrates a graphical representation of the physical response characteristics of the secondary piston, depicting a combination of impulse and amplitude modulation of the secondary piston, according to the present invention;

FIG. 7 illustrates a partial schematic side view of the rapid response energy extracting system, depicting the primary and secondary pistons in terms of linear displacement, according to the present invention;

5

FIG. 7A illustrates a graphical representation of the linear displacement of the secondary piston with respect to heavier and lighter loads, according to the present invention;

FIG. 8 illustrates a partial schematic side view of the rapid response energy extracting system, depicting a non-combustion system, according to a third embodiment of the present invention; and

FIG. 9 illustrates an elevation view of a representative use of the present invention, as used in a wearable exoskeleton frame.

DETAILED DESCRIPTION

For the purposes of promoting an understanding of the principles of the present invention, reference will now be made to the exemplary embodiments illustrated in the drawings, and specific language will be used to describe the same. It will nevertheless be understood that no limitation of the scope of the invention is thereby intended. Any alterations and further modifications of the inventive features illustrated herein, and any additional applications of the principles of the invention as illustrated herein, which would occur to one skilled in the relevant art and having possession of this disclosure, are to be considered within the scope of the invention.

Referring first to FIG. 1, a simplified schematic view of a rapid response energy extracting system 100 is illustrated. Such a system 100 may partially include a typical internal combustion (“IC”) engine, such as a four stroke spark ignition IC engine. Other types of engines may also be utilized with the present invention, such as compression ignition IC engines, two stroke IC engines, non-combustion engines or any other suitable engine. For purposes of simplicity, rapid response energy extracting system 100 is illustrated here in conjunction with a typical four stroke spark ignition IC engine, wherein a single chamber 110 is depicted with the present invention.

The chamber 110 is defined by chamber walls 105 and includes one or more intake ports 112 for receiving a fuel, 114 and an oxidizer such as air or oxygen, separately or as a mixture, and an out-take port 122 for releasing combustive exhaust gases 124. Each of the intake port 112 and the out-take port 122 includes a valve (not shown), which are each configured to open and close at specified times to allow fuel 114 and exhaust 124 to enter and exit the chamber 110, respectively. The chamber 110 includes a primary piston 130, a secondary piston 140 and a combustion portion 120 therebetween. The primary piston 130 is interconnected to a piston rod 132, which in turn is interconnected to a crank shaft 134. The primary piston 130 is sized and configured to move linearly within the chamber 110 for converting linear movement 138 from the primary piston 130 to the crank shaft 134 into rotational energy 136. Such rotational energy 136 may be used to power a wide range of external applications, such as any type of application that typically utilizes an IC combustion engine.

The linear movement 138 of the primary piston 130 takes place between a top dead center (“TDC”) position and a bottom dead center (“BDC”) position. The TDC position occurs when the piston 130 has moved to its location furthest from the crank shaft 134 and the BDC position occurs when the primary piston 130 has moved to its location closest to the crank shaft 134. The linear movement of the primary piston 130 between the TDC position and the BDC position may be generated by cyclic combustion in the combustion portion 120 of the chamber 110. Primary piston 130 may also move linearly within chamber 110 by other suitable means, such as an electric motor using energy from a battery.

6

A four stroke cycle of an IC engine begins with the piston 130 located at TDC. As the piston 130 moves toward BDC, a fuel 114 and oxidizer or combustible mixture is introduced into the chamber 110 through intake port 112, which may include one or more openings and may also be a variable opening for varying the flow and amount of fuel 114 into the chamber 110. Once the fuel 114 enters the chamber 110, the intake port 112 is closed and the piston 130 returns toward TDC, compressing the combustible mixture and/or fuel 114 in the chamber 110. An ignition source 116, controlled by a controller 115, supplies a spark at which point the compressed fuel combusts and drives the piston 130 back to BDC. The controller 115 may also be configured to control the valves (not shown) at the intake port 112 and the out-take port 122 to control the rate by which fuel 114 may feed the chamber 110. As the piston 130 returns again toward TDC, combustive exhaust gases 124 are forced through out-take port 122. The out-take port 122 is then closed, and intake port 112 is opened, and the four stroke cycle may begin again. In this manner, a series of combustion cycles powers the crank shaft 134, which provides rotational energy 136 to an external application.

According to the present invention, chamber 110 also includes a secondary piston 140 having a secondary piston rod 142 extending therefrom. The secondary piston 140 includes a face, or energy receiving end 144, and the secondary piston rod 142 is coupled to an energy transferring portion 146. The energy receiving end 144 may be positioned in chamber 110 to face primary piston 130 so that the longitudinal movement of the primary piston 130 and the secondary piston 140 corresponds with a longitudinal axis of chamber 110. In an inactive position, the energy receiving end 144 of the secondary piston 140 may be biased in a substantially sealing, retracted position against a lip or some other suitable sealing means, biased by a spring or by another suitable biasing force, such as a pressure reservoir, so that the secondary piston 140 is biasingly positioned prior to introducing fuel into the combustion chamber 110 or prior to combustion during cyclic combustion of the system 100.

One important aspect of the present invention is that the secondary piston 140 includes a substantially lower inertia than that of the primary piston 130. Such a substantially lower inertia positioned adjacent the combustion portion 120 of the chamber 110 facilitates a rapid response to combustion, which provides linear movement 148 of the secondary piston 140 along the longitudinal axis of the chamber 110. Because the inertia of the secondary piston 140 is much lower than the inertia of the primary piston 130, the secondary piston 140 can efficiently extract a large fraction of the energy created by the combustion before it is otherwise lost to inefficiencies inherent in IC engines. With this arrangement, the energy receiving end 144 of the secondary piston 140 is sized, positioned and configured to react to combustion in the chamber 110 so as to provide linear movement 148 to the energy receiving end 144 to then act upon the energy transferring portion 146 of the system 100.

Referring now to FIG. 2, the energy transferring portion 146 may include and/or may be coupled with any number of energy conversion devices. In particular, the energy transferring portion 146 is configured to transfer the linear movement of the secondary piston 140 to any one of hydraulic energy, pneumatic energy, electric energy and/or mechanical energy. Transferring linear motion into such various types of energy is well known in the art.

For example, in a hydraulic system 160, linear motion via the secondary piston rod 142 transferred to a hydraulic

piston **164** in a hydraulic chamber **162** may provide hydraulic pressure and flow **168**, as well known in the art. Similarly, in a pneumatic system **170**, the secondary piston rod **142** may provide linear motion to a pneumatic piston **174** in a pneumatic chamber **172** to provide output energy in the form of pneumatic pressure and gas flow **178**.

Other systems may include an electrical system **180** and a mechanical system **190**. As well known in the art, in an electrical system **180**, the linear motion of secondary piston rod **142** may be interconnected to an armature with a coil wrapped therearound, wherein the armature reciprocates in the coil to generate an electrical energy output **188**. Furthermore, in the mechanical system, linear motion from secondary piston rod **142** may be transferred to rotational energy **198** with a pawl **192** pushing on a crank shaft **194** to provide rotational energy **198**. Additionally, the secondary piston rod **142** may be directly interconnected to the crank shaft **194** to provide the rotational energy **198**. Other methods of converting energy will be apparent to those skilled in the art. For example, rotational electric generators, gear driven systems, and belt driven systems can be utilized by the energy transferring portion **146** the present invention.

Referring now to FIG. 3, there is illustrated a second embodiment of the rapid response energy extracting system **200**. The second embodiment is similar to the first embodiment, except the chamber **210** defines a first compartment **254** and a second compartment **256** with a divider portion **250** disposed therebetween. The divider portion **250** defines an aperture **252** therein, which aperture **252** extends between the first compartment **254** and the second compartment **256**. With this arrangement, the primary piston **230** is positioned in the first compartment **254** and the secondary piston **240** is positioned in the second compartment **256**. The intake port **212** allows fuel **214** and/or combustible mixture to enter the first compartment **254**. The fuel **214** and/or combustible mixture are pushed through the aperture **252** from the first compartment **254** into the second compartment **256** via the primary piston **230**. The fuel **214** and/or combustible mixture is compressed at a combustion portion **220** of the chamber **210**, which is directly adjacent the secondary piston **240**. An ignition source **216** then fires the fuel for combustion, wherein the secondary piston **240** moves linearly, as indicated by arrow **248**, with a rapid response to the combustion. The combustible exhaust **224** then exits through the out-take port **222**. It should be noted that the first compartment **254** and second compartment **256** may be remote from each other, wherein the first and second compartments **254** and **256** may be in fluid communication with each other via a tube.

In the second embodiment, the primary piston **230** may reciprocate via combustion or an electric power source to push the fuel **214** from the first compartment to the second compartment of chamber **210**. By having a divider portion **250**, the combustion at the combustion portion **220** of the chamber **210** can be at least partially, or even totally, isolated from the primary piston **230**. Depending on the requirements of the system **200**, the controller **215** may be configured to open or close aperture **252** at varying degrees to isolate combustion from the primary piston **230**. As such, in the instance of total isolation, a maximum amount of energy to the secondary piston **240** may be transferred by a rapid response to combustion. It is also contemplated that the primary piston **230** in the first compartment **254** may include a positive displacement compressor and/or an aerodynamic compressor, such as a centrifugal compressor.

Referring now to FIGS. 1 and 4, a graphical diagram of the physical response characteristics of the secondary piston

140 with respect to the primary piston **130** is illustrated. Line **330** represents the linear movement **138** of the primary piston **130**, reciprocating between the TDC **350** and the BDC **352** positions thereof. Line **330** illustrates one complete cycle, for a four cycle IC engine, in which the primary piston **130** travels between the TDC **350** and the BDC **352** positions twice, with one combustion event occurring immediately after the primary piston **130** reaches TDC the first time. Line **340** illustrates the linear displacement of the secondary piston **140**. As indicated, the secondary piston **140** reaches substantially full displacement within at least 45 degrees, and even up to 30 degrees, of the primary piston **140** descending from TDC **350**, wherein the secondary piston **140** completes one cycle much more rapidly than does the primary piston **130**.

Turning now to line **360**, a relative indication of the temperature rise and fall in the chamber **110** due to combustion and heat loss, respectively, with respect to the linear positions of the primary piston **130** and the secondary piston **140** is shown. Immediately after ignition of the fuel **114** and/or combustible mixture, when the primary piston **130** is proximate the TDC **350** position, combustion facilitates a dramatic increase in temperature. As well known, IC engines are designed to convert the thermal energy created by combustion into linear movement of the primary piston, which is in turn converted into rotational energy in the drive shaft. However, much of the thermal energy created in conventional internal combustion engines is lost due to heat escaping into the engine walls surrounding the combustion chamber and in exhaust gases. Even the most efficient internal combustion engines rarely reach efficiency rates of more than 35%. Consequently, more than half of the energy available from the combusted fuel is lost in the form of heat through the walls and piston via conduction and radiation, as well as heat released through the exhaust.

The heat rise and heat loss illustrated by the rising and dropping line **360**, representing combustion, depicts the time during which energy is available in the form of thermal energy and the time in which the primary piston **130** should be extracting the thermal energy. Time t_2 indicates the time period during which a majority of the thermal energy is available for conversion by the primary piston. Time t_1 indicates the time period during which the primary piston **130** is moving from the TDC **350** to BDC **352** positions. It is during the period t_1 that the primary piston **130** should be converting energy from the combustion process. As indicated by the difference between the two time periods t_1 and t_2 , most of the thermal energy from the combustion escapes prior to the primary piston **130** reaching a median **354** of its travel between the TDC **350** to BDC **352** positions.

However, according to the present invention, the secondary piston **140** substantially completes its useful energy extraction cycle before the expiration of time period t_2 . In particular, as indicated by line **340**, at least 90% of the energy extracted by the secondary piston **140** is extracted within at least 45 degrees, and even at least 30 degrees, of the primary piston **140** descending from the TDC **350** position. Because the secondary piston **140** moves much more rapidly than does the primary piston **130**, it can convert a much greater percentage of the thermal energy into linear motion before the thermal energy is lost to the heat sink formed by the walls, primary piston, and other components of the IC engine. Additionally, because the secondary piston **140** acts independently of the primary piston **130** and because the secondary piston **140** has a substantially lower inertia than the primary piston **130**, the secondary piston **140** reacts to combustion with a very short response time without being inhibited by the primary piston **130**.

For example, an IC engine having operating characteristics running at 3000 revolutions per minute, t_1 would be approximately 10 milliseconds, or 0.010 seconds, and t_2 would be approximately 3 milliseconds. Because the secondary piston 140 can be operated independently of the primary piston 130, the secondary piston 140 can be operated with a response time of approximately 3 milliseconds or potentially even at a shorter response time. In other words, the secondary piston 140 can both begin and stop extracting energy from the combustion cycles of the system 100 within at least a 3 millisecond time period. Higher cycle rate can be achieved by operating the primary piston 130 at a higher speed (i.e., higher number of rpms).

Turning to FIGS. 1 and 5, physical response characteristics, such as impulse modulation and superior bandwidth provided by the secondary piston 140 with respect to the primary piston 130 are illustrated. In particular, line 430 depicts the primary piston 130 reciprocating repeatedly or substantially continuously with a substantially fixed displacement between the TDC and BDC positions. As the primary piston 130 continuously reciprocates, the controller 115 is configured to control combustion at selective cycles of reciprocation of the primary piston 130 in which combustion is selected are illustrated in corresponding lines 440. Lines 440 indicate a portion of energy extracted by the secondary piston 140 from the selected cycles of the primary piston 130 where the controller 115 controls or initiates combustion (i.e., amplitude modulation, impulse modulation, and frequency modulation). The flat portion 442 of line 440 corresponds to the absence of combustion, showing no displacement and energy extraction from the secondary piston 140.

As shown, the primary piston 130 continuously reciprocates in the chamber 110, wherein the controller 115 selectively controls particular reciprocating cycles in which combustion occurs. As such, the cycles selected for combustion to facilitate the extraction of a portion of the combustion energy may include each reciprocation cycle of the primary piston or, as indicated, an impulse modulation. Such an impulse modulation provides thermal energy extracted over one or more selected cycles of the primary piston 130 as well as one or more sequence of selected cycles where no energy is extracted.

As can be readily recognized by one of ordinary skill in the art, the impulse modulation illustrates that the rate by which energy may be extracted and then stopped from extracting energy is extremely rapid. Such ability to extract energy and then rapidly stop extracting, and then again rapidly extract energy at selected cycles of the primary piston 130 provides a favorable bandwidth far superior to the bandwidth of the energy extraction and conversion of the primary piston 130. Thus, energy may be provided and stopped with a rapid response and with favorable bandwidth by the controller 115 controlling the combustion at selected cycles and the secondary piston 140 reacting to the combustion, as indicated by line 440. Furthermore, referencing FIGS. 1 and 6, the controller 115 may control the fuel 114 and combustion at selected cycles of the primary piston 130 so that the secondary piston 140 extracts a portion of the combustion energy to provide amplitude modulation and, further, impulse amplitude modulation 540. Further, a person of ordinary skill in the art will readily recognize that the controller 115 may control the fuel 114 and combustion at selected cycles so as to provide frequency modulation and even frequency, impulse modulation, or, even frequency, amplitude modulation.

Turning to FIG. 7, there is illustrated relative linear movement with respect to the primary piston 630 and the secondary piston each in chamber 610. In particular, the linear movement 638 of the primary piston 630 in chamber 610 is substantially constant with a displacement D1. On the other hand, the linear movement 648 of the secondary piston may be variable in length referenced as displacement D2. Such variable length of displacement D2 of the secondary piston may change with respect to a load 650 of which the energy extracted by the secondary piston is acting upon. Other factors that effect the displacement D2 of the secondary piston 640 relate to inertia of the mass of secondary piston 640 and its piston rod 642. As previously set forth, the effective inertia of the primary piston 630, a crank assembly is greater than the effective inertia of the secondary piston 640 by a ratio of at least 5:1, and even at least 10:1, at least during the time period when a portion of energy is extracted from combustion by the secondary piston 640. Since the inertia of the secondary piston 640 is less than the inertia of the primary piston 630, the secondary piston 640 is able to react with a rapid response. In this manner, the displacement D2 of the secondary piston 640 is variable in length, in which the displacement D2 naturally matches and corresponds with at least the load 650 to which the extracted energy is acting upon as well as with respect to the combustion force acting on the secondary piston 640 at combustion. D2' and D2'' represent a variety of lengths which form a continuum of values, corresponding to a continuous transmission system. This is illustrated in FIG. 7A, wherein D2' corresponds to a heavier load, and D2'' relates to a lighter load, thereby eliminating the need for a separate transmission device as is typically required for an IC engine.

Referencing FIG. 8, the rapid response energy extracting system 700 may be provided in a non-combustion engine, according to a third embodiment of the present invention. The system 700 includes a chamber 710 with a primary piston 730 and a secondary piston 740. Instead of internal combustion provided by fuel and oxygen, a fluid 714, such as a monopropellant or hydrogen peroxide, may enter through an intake port 712 of the chamber 710. The fluid 714 may pass through or over a reaction member 720, such as a catalyst or heat-exchanger. Such a catalyst may include silver, silver alloy, and/or a silver/ceramic material. As the fluid 714 passes over the reaction member 720, a rapid non-combustive reaction results, which may include rapid decomposition of the fluid 714 and/or vaporization of the fluid 714. As in the IC engine, such rapid non-combustive reaction causes a rapid response from the secondary piston 740 for extracting a portion of energy from the rapid non-combustive reaction. In this system, the primary piston 740 may reciprocate and function similar to the primary piston in the IC engine or, alternatively, the primary piston 730 may simply act as a means for pumping fluid in and out of the chamber 710.

While the preceding discussion focused on the characteristics of four stroke internal combustion engines as primary power sources, the present invention is not restricted to use with an internal combustion engine. The present invention can be utilized with any primary power source that delivers variable pulsating pressure. For example, two-stroke internal combustion engines, diesel engines, Stirling engines, external combustion engines and heat engines can all be used as primary power sources for the rapid response power conversion device. The above described present invention may be used to provide energetic autonomy to power sources used in robotics. Robots could be powered by self-contained fuel consumption devices which are not teth-

ered to any primary power source. Because the present invention allows for direct conversion of fuel into rapid response energy, any intermediate storage device such as a large hydraulic accumulator or electric battery would no longer be necessary, eliminating large weight additions to the robot without sacrificing the speed with which the robot could access power.

For example, the present invention could be used to provide energetic autonomy to power sources used in robotics. Robots could be powered by self-contained fuel consumption devices which are not tethered to any primary power source. Because the present invention allows for direct conversion of fuel into rapid response energy, any intermediate storage device such as a hydraulic accumulator or electric battery would no longer be necessary, eliminating large weight additions to the robot without sacrificing the speed with which the robot could access power.

In addition to providing a lightweight, energetically autonomous rapid response power source for use in robotics, the present invention could be used in much the same way to assist human movement. Shown generally at **800** in FIG. **9** is a wearable exoskeletal frame for use by a human. A central control unit **802** can serve as a fuel storage device, power generation center and/or a signal generation/processing center. Shown at **804**, attached at **808** to the joints of the exoskeleton **809** is an actuator **806**. The cylinder (not shown) within the actuator can be extended or retracted to adjust the relative position of the upper and lower leg segments, **816** and **818**, respectively, of the exoskeletal frame. The actuator **806** can be driven by a rapid response power conversion device **810**. The rapid response power conversion device can be a small internal combustion engine supplied by fuel from fuel line **812** and controlled by an input/output signal line **814**. The system can be configured such that an actuator and a power conversion device are located at each joint of the exoskeletal frame and are controlled by signals from the master control unit **802**. Alternately, the system could be configured such that one or more master power conversion devices are located in the central control unit **802** for selectively supplying power to actuators located at each joint of the exoskeleton. Sensors (not shown) could be attached to various points of the exoskeleton to monitor movement and provide feedback. Also, safety devices such as power interrupts (not shown) can be included to protect the safety of the personnel wearing the exoskeletal frame.

The wearable exoskeletal frame could be used in many applications. In one embodiment, the frame could be configured to assist military personnel in difficult or dangerous tasks. The energetically autonomous rapid response power conversion device can allow conventional primary power sources to be used to enhance the strength, stamina and speed of personnel without requiring that the personnel be tethered to a primary power source. The wearable frame could reduce the number of personnel required in dangerous or hazardous tasks and reduce the physical stress experienced by personnel when executing such tasks. The wearable frame could also be configured for application-specific tasks which might involve exposure to radiation, gas, chemical or biological agents.

The wearable frame could also be used to aid physically impaired individuals in executing otherwise impossible tasks such as sitting, standing or walking. The rapid response power conversion device could serve as a power amplifier, amplifying small motions and forces into controlled, large motions and forces. By strategically placing sensors and control devices in various locations on the frame, individu-

als who are only capable of applying very small amounts of force could control the motion of the frame. Because the rapid response power conversion device is energetically autonomous, physically impaired individuals could be given freedom of movement without being tethered to a power source. The rapid response power conversion device would also be capable of producing the small, discrete movements necessary to imitate human movement. Safety devices such as power interrupts could be built into the system to prevent unintentional movement of the frame and any damage to the individual wearing the frame.

In addition to the previous applications, the present invention can be used in any number of applications that require rapid response power without tethering the application to a primary power source. Examples can include power driven wheelchairs, golf carts, automobiles, skateboards, scooters, ultra-light aircraft, and other motorized vehicles, and generally any application which leverages mechanical energy and which would benefit by energetic autonomy.

It is to be understood that the above-described arrangements are only illustrative of the application of the principles of the present invention. Numerous modifications and alternative arrangements may be devised by those skilled in the art without departing from the spirit and scope of the present invention and the appended claims are intended to cover such modifications and arrangements. Thus, while the present invention has been shown in the drawings and fully described above with particularity and detail in connection with what is presently deemed to be the most practical and preferred embodiment(s) of the invention, it will be apparent to those of ordinary skill in the art that numerous modifications, including, but not limited to, variations in size, materials, shape, form, function and manner of operation, assembly and use may be made, without departing from the principles and concepts of the invention as set forth above.

What is claimed is:

1. An internal combustion (IC) engine comprising:

a chamber having a piston, at least one fluid port coupled to said chamber for supplying fluid thereto and an out-take port, said piston and said at least one fluid port configured to provide a variable pressure to said chamber, said piston and said fluid configured to at least partially facilitate combustion to provide energy from said combustion in a combustion portion of said chamber;

a controller for controlling said combustion in said chamber; and

a rapid response component in fluid communication with said chamber, said rapid response component situated adjacent said combustion portion of said chamber, said rapid response component configured to draw a portion of said energy from said combustion in said chamber;

said rapid response component comprising a secondary piston disposed in said chamber, said secondary piston comprising an energy receiving portion and an energy transferring portion, said energy receiving portion configured to draw said portion of said energy from said combustion in said chamber.

2. The IC engine of claim 1, wherein said energy transferring portion is configured to transfer said portion of said energy from said combustion to at least one form of energy selected from the group consisting of hydraulic energy, pneumatic energy, electric energy and mechanical energy.

3. The IC engine of claim 1, further comprising a secondary energy conversion system operatively coupled to

13

said energy transferring portion of said secondary piston, said secondary energy conversion system being selected from the group consisting of a hydraulic system, a pneumatic system, an electric generator system and a mechanical system.

4. The IC engine of claim 1, wherein said controller comprises a spark ignition source configured to at least partially facilitate said combustion in said chamber.

5. The IC engine of claim 1, wherein said controller comprises a fuel controller for combining a fuel with an oxidizer to at least partially facilitate said combustion in said chamber.

6. The IC engine of claim 5, wherein said oxidizer is selected from the group consisting of pure oxygen and air.

7. The IC engine of claim 1, wherein said controller includes structure for releasing a fuel into compressed oxidizer fluid to at least partially facilitate said combustion in said chamber.

8. The IC engine of claim 1, wherein said chamber is configured to operate in combination with an engine selected from the group consisting of a spark ignition IC engine and a compression ignition IC engine.

9. The IC engine of claim 1, wherein said rapid response component configured to draw said portion of said energy from said chamber during a time period from a proximate instant of said combustion and prior to said piston reciprocating to a position at a median between a top dead center position and a bottom dead center position.

10. The IC engine of claim 1, wherein said chamber houses at least one of said piston and said secondary piston.

11. The IC engine of claim 1, wherein said piston is configured to substantially continuously reciprocate in said chamber.

12. The IC engine of claim 11, wherein said controller is configured to initiate said combustion at selected cycles of one or more cycles, wherein said selected cycles are non-continuous compared to that of said piston substantially continuously reciprocating in said chamber.

13. An internal combustion (IC) engine comprising:

a chamber having a piston, at least one fluid port coupled to said chamber for supplying fluid thereto and an out-take port, said piston and said at least one fluid port configured to provide a variable pressure to said chamber, said piston and said fluid configured to at least partially facilitate combustion to provide energy from said combustion in a combustion portion of said chamber;

a controller for controlling said combustion in said chamber; and

a rapid response component in fluid communication with said chamber, said rapid response component situated adjacent said combustion portion of said chamber, said rapid response component configured to draw a portion of said energy from said combustion in said chamber; said rapid response component being configured to provide greater bandwidth than direct bandwidth supplied directly by the piston of said IC engine.

14. An internal combustion engine comprising:

a chamber having a piston, at least one fluid port coupled to said chamber for supplying fluid thereto and an out-take port, said piston and said at least one fluid port configured to provide a variable pressure and temperature to said chamber, said piston configured to reciprocate in said chamber between a top dead center position and a bottom dead center position, each reciprocation of said piston defining a cycle, said piston and

14

said fluid configured to at least partially facilitate combustion to provide energy from said combustion in a combustion portion of said chamber;

a controller for controlling said combustion in said chamber; and

a rapid response component in fluid communication with said chamber, said rapid response component configured to draw a portion of said energy from said chamber during a time period from a proximate instant of said combustion and prior to said piston being positioned at a median between said top dead center position and said bottom dead center position;

said proximate instant of said combustion being immediately prior to combustion.

15. The IC engine of claim 14, wherein said piston is configured to substantially continuously reciprocate in said chamber.

16. The IC engine of claim 15, wherein said controller is configured to initiate said combustion at selected cycles of one or more cycles, wherein said selected cycles are non-continuous compared to that of said piston substantially continuously reciprocating in said chamber.

17. An internal combustion engine comprising:

a chamber having a piston, at least one fluid port coupled to said chamber for supplying fluid thereto and an out-take port, said piston and said at least one fluid port configured to provide a variable pressure and temperature to said chamber, said piston configured to reciprocate in said chamber between a top dead center position and a bottom dead center position, each reciprocation of said piston defining a cycle, said piston and said fluid configured to at least partially facilitate combustion to provide energy from said combustion in a combustion portion of said chamber;

a controller for controlling said combustion in said chamber; and

a rapid response component in fluid communication with said chamber, said rapid response component configured to draw a portion of said energy from said chamber during a time period from a proximate instant of said combustion and prior to said piston being positioned at a median between said top dead center position and said bottom dead center position;

said proximate instant of said combustion being immediately subsequent to combustion.

18. An internal combustion engine comprising:

a chamber having a piston, at least one fluid port coupled to said chamber for supplying fluid thereto and an out-take port, said piston and said at least one fluid port configured to provide a variable pressure and temperature to said chamber, said piston configured to reciprocate in said chamber between a top dead center position and a bottom dead center position, each reciprocation of said piston defining a cycle, said piston and said fluid configured to at least partially facilitate combustion to provide energy from said combustion in a combustion portion of said chamber;

a controller for controlling said combustion in said chamber; and

a rapid response component in fluid communication with said chamber, said rapid response component configured to draw a portion of said energy from said chamber during a time period from a proximate instant of said combustion and prior to said piston being positioned at a median between said top dead center position and said bottom dead center position;

15

said rapid response component drawing majority of said portion of said energy from said chamber within 45 degrees of said piston descending from said top dead center position.

19. An internal combustion engine comprising:

a chamber having a piston, at least one fluid port coupled to said chamber for supplying fluid thereto and an out-take port, said piston and said at least one fluid port configured to provide a variable pressure and temperature to said chamber, said piston configured to reciprocate in said chamber between a top dead center position and a bottom dead center position, each reciprocation of said piston defining a cycle, said piston and said fluid configured to at least partially facilitate combustion to provide energy from said combustion in a combustion portion of said chamber;

a controller for controlling said combustion in said chamber; and

a rapid response component in fluid communication with said chamber, said rapid response component configured to draw a portion of said energy from said chamber during a time period from a proximate instant of said combustion and prior to said piston being positioned at a median between said top dead center position and said bottom dead center position;

said rapid response component drawing at least 90% of said portion of said energy from said chamber within 45 degrees of said piston descending from said top dead center position.

20. An internal combustion engine comprising:

a chamber having a piston, at least one fluid port coupled to said chamber for supplying fluid thereto and an out-take port, said piston and said at least one fluid port configured to provide a variable pressure and temperature to said chamber, said piston configured to reciprocate in said chamber between a top dead center position and a bottom dead center position, each reciprocation of said piston defining a cycle, said piston and said fluid configured to at least partially facilitate combustion to provide energy from said combustion in a combustion portion of said chamber;

a controller for controlling said combustion in said chamber; and

a rapid response component in fluid communication with said chamber, said rapid response component configured to draw a portion of said energy from said chamber during a time period from a proximate instant of said combustion and prior to said piston being positioned at a median between said top dead center position and said bottom dead center position;

said rapid response component being coupled to a load selected from the group consisting of a hydraulic system, a pneumatic system, an electric generator system and a mechanical system.

21. An internal combustion engine comprising:

a chamber having a piston, at least one fluid port coupled to said chamber for supplying fluid thereto and an out-take port, said piston and said at least one fluid port configured to provide a variable pressure and temperature to said chamber, said piston configured to reciprocate in said chamber between a top dead center position and a bottom dead center position, each reciprocation of said piston defining a cycle, said piston and said fluid configured to at least partially facilitate combustion to provide energy from said combustion in a combustion portion of said chamber;

16

a controller for controlling said combustion in said chamber; and

a rapid response component in fluid communication with said chamber, said rapid response component configured to draw a portion of said energy from said chamber during a time period from a proximate instant of said combustion and prior to said piston being positioned at a median between said top dead center position and said bottom dead center position;

said rapid response component being configured to convert energy from said combustion to another form of energy selected from the group consisting of hydraulic energy, pneumatic energy, electric energy and mechanical energy.

22. An internal combustion engine comprising:

a chamber having a piston, at least one fluid port coupled to said chamber for supplying fluid thereto and an out-take port, said piston and said at least one fluid port configured to provide a variable pressure and temperature to said chamber, said piston configured to reciprocate in said chamber between a top dead center position and a bottom dead center position, each reciprocation of said piston defining a cycle, said piston and said fluid configured to at least partially facilitate combustion to provide energy from said combustion in a combustion portion of said chamber;

a controller for controlling said combustion in said chamber; and

a rapid response component in fluid communication with said chamber, said rapid response component configured to draw a portion of said energy from said chamber during a time period from a proximate instant of said combustion and prior to said piston being positioned at a median between said top dead center position and said bottom dead center position;

said controller being configured to control activation of said rapid response component.

23. An internal combustion engine comprising:

a chamber having a piston, at least one fluid port coupled to said chamber for supplying fluid thereto and an out-take port, said piston and said at least one fluid port configured to provide a variable pressure and temperature to said chamber, said piston configured to substantially continuously reciprocate in said chamber between a top dead center position and a bottom dead center position, each reciprocation of said piston defining a cycle, said reciprocating piston and said fluid configured to at least partially facilitate combustion to provide energy from said combustion in a combustion portion of said chamber;

a controller for controlling said combustion in said chamber, said controller configured to provide said combustion to said chamber at selected cycles of one or more cycles of said reciprocating piston, wherein said selected cycles are non-continuous compared to that of said piston substantially continuously reciprocating in said chamber; and

a rapid response component in fluid communication with said chamber, said rapid response component situated adjacent said combustion portion of said chamber, said rapid response component drawing a portion of said energy from said combustion in said chamber controlled by said controller.

24. The IC engine of claim **23**, wherein said controller is configured to control a response of said rapid response component.

25. The IC engine of claim 23, wherein said portion of said energy comprises additional energy than that of said energy drawn from said piston.

26. The IC engine of claim 23, wherein said controller is configured to activate said rapid response component.

27. The IC engine of claim 23, wherein said controller controlling said combustion in said chamber at said selected cycles initiates said portion of said energy to be transferred to an additional energy system selected from the group consisting of a hydraulic system, a pneumatic system, an electric generator system and a mechanical system.

28. The IC engine of claim 23, wherein said rapid response component is activated by said combustion at said selected cycles to provide rapid response power controlled by said controller.

29. The IC engine of claim 23, wherein said portion of said energy drawn from said combustion provides rapid response power corresponding to said combustion of said selected cycles, wherein said rapid response power is provided during a combustion cycle of said piston and said rapid response power is rapidly eliminated during a non-combustion cycle.

30. The IC engine of claim 29, wherein said rapid response power is provided to a load selected from at least one of the group consisting of a hydraulic system, a pneumatic system, an electric generator system and a mechanical system, each system of which responds rapidly with respect to said selected cycles of combustion.

31. An internal combustion (IC) engine comprising:

a chamber having a piston, at least one fluid port coupled to said chamber for supplying fluid thereto and an out-take port, said piston and said at least one fluid port configured to provide a variable pressure to said chamber, said piston configured to reciprocate in said chamber continuously between a top dead center position and a bottom dead center position with a substantially fixed displacement, said piston and said fluid configured to at least partially facilitate combustion to provide energy from said combustion in a combustion portion of said chamber;

a controller for controlling said combustion in said chamber; and

a rapid response component having a secondary piston in fluid communication with said chamber, said rapid response component situated adjacent said combustion portion of said chamber to draw a portion of said energy from said combustion, said secondary piston configured to displace at variable lengths based at least in part by a load coupled to said secondary piston.

32. The IC engine of claim 31, wherein said piston includes a first mass and said secondary piston includes a second mass, wherein a first effective inertia of said first mass is greater than a second effective inertia of said second mass by a ratio of at least 5:1 at least during said portion of said energy being transferred to said rapid response component.

33. The IC engine of claim 31, wherein said rapid response component draws at least a majority of said portion

of said energy from said chamber within 45 degrees of said piston descending from said top dead center position.

34. The IC engine of claim 31, wherein said rapid response component draws at least 90% of said portion of said energy from said chamber within 45 degrees of said piston descending from said top dead center position.

35. The IC engine of claim 31, wherein said piston includes a first mass and said secondary piston includes a second mass, wherein a first effective inertia of said first mass is greater than a second effective inertia of said second mass.

36. The IC engine of claim 31, further comprising a continuous transmission system configured to provide said variable lengths of said secondary piston, variable at least in part as a function of said load.

37. A method for extracting additional energy from an IC engine, the method comprising:

providing a chamber having a piston, at least one fluid port coupled to said chamber for supplying fluid thereto and an out-take port, said piston and said at least one fluid port configured to provide a variable pressure to said chamber, said piston configured to reciprocate in said chamber between a top dead center position and a bottom dead center position, each reciprocation of said piston defining a cycle, said piston and said fluid configured to at least partially facilitate combustion to provide energy from said combustion in a combustion portion of said chamber;

providing a rapid response component;

positioning said rapid response component to be in fluid communication with said chamber and adjacent said combustion portion of said chamber; and

controlling said combustion in said chamber with a controller interconnected to said chamber;

said controlling comprising controlling said controller to provide said combustion to said chamber at selected cycles of one or more cycles of said piston such that said selected cycles are non-continuous compared to that of said piston continuously reciprocating in said chamber.

38. The method of claim 37, further comprising configuring said rapid response component to draw a portion of said energy from said combustion in said chamber from a proximate instant of said combustion and prior to said piston being positioned at a median between said top dead center position and said bottom dead center position.

39. The method of claim 38, wherein said configuring comprises configuring said rapid response component to draw a majority of said portion of said energy from said chamber within 45 degrees of said piston descending from said top dead center position.

40. The method of claim 39, wherein said configuring comprises configuring said rapid response component to draw at least 90% of said portion of said energy from said chamber within 45 degrees of said piston descending from said top dead center position.